

pursang
Mk7

125



250



360



BULTACO



CARACTERISTICAS

MOTOR: 2 tiempos y 1 cilindro
Diámetro x carrera (mm.)
Cilindrada (cc.)
Relación de compresión
Potencia máxima (HP @ rpm.)

CARBURADOR

CAMBIO: 5 velocidades
en toma constante
(Especial para 125)

ENCENDIDO

Rotor

TRANSMISIONES

Cadena primaria 3/8"
Cadena secundaria 5/8"

EMBRAGUE

SUSPENSIONES con
amortiguadores hidráulicos

Delantera
Trasera

NEUMATICOS DE CROSS

Delantero
Trasero

FRENOS de expansión interna

Delantero
Trasero

MEDIDAS GENERALES

Largo total
Distancia entre ejes
Manillar, alto x ancho
Altura sillín
Altura mínima
Altura estribos
Capacidad depósito
Peso en vacío

PURSANG MK7

125
51,5 x 60
124,98
14:1
25,1 @ 9800
AMAL 627

250
72 x 60
244,29
12:1
40,8 @ 8500
AMAL 1036

I. 0.376:1 - II. 0.513:1 - III. 0.670:1 - IV. 0.832:1 - V. 1:1
I. 0.412:1 - II. 0.561:1 - III. 0.697:1 - IV. 0.833:1 - V. 1:1

Electrónico - Electronic

Doble, Double

Por cadenas - By chains

ASA 2035/52
ESPECIAL 55 CROSS

Discos múltiples en baño de aceite - Multiple plates in oil bath

Telescópica de 165 mm. - Telescopic, 6,5" Travel
Basculante - Swinging arm

3,00 x 21"
4,00 x 18"

125 x 25 mm.
140 x 30 mm.

2100 mm. = 82,6"
1420 mm. = 55,9"
1060 x 860 mm. = 41,7 x 33,8"
790 mm. = 31,1"
245 mm. = 9,6"
300 mm. = 10,8"
7 litros = 1,85 U. S. gallons
89 kgs.
196 lbs.

95 kgs.
209 lbs.

SPECIFICATIONS

ENGINE: 2 stroke & 1 cylinder
Bore and stroke (mm.)
Displacement (cc.)
Compression ratio
Bhp @ rpm.

CARBURETER

GEARBOX: 5 speed
in constant - mesh
Only for 125)

IGNITION

TRANSMISSIONS
3,8" Primary chain
5,8" Secondary chain

CLUTCH

SUSPENSIONS with
hydraulic dampening

Front
Rear

KNOBBY TYRES

Front
Rear

BRAKES, internal expansion

Front
Rear

GENERAL DETAILS

Overall length
Wheelbase
Handlebars, height & width
Seat height
Ground clearance
Footrest height
Gas-Tank capacity
Empty weight

Modelos n.ºs 117, 120 y 121

Art.º 120-34-002

CRT - Dep. Legel: B. 12.920 - 74
Printed in Spain

COMPANIA ESPAÑOLA DE MOTORES, S. A.
San Adrián de Besós - Barcelona - SPAIN

RESERVADO EL DERECHO DE INTRODUCIR CUALQUIER MODIFICACION

CONSTANT IMPROVEMENTS WILL SUBJECT SPECIFICATIONS TO CHANGE WITHOUT NOTICE